UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/706,282	11/13/2003	Aviv Bachar	82031-0016US	5641

27623   7590   11/12/2008
OHLANDT, GREELEY, RUGGIERO & PERLE, LLP
ONE LANDMARK SQUARE, 10TH FLOOR
STAMFORD, CT 06901

EXAMINER
COLUCCI, MICHAEL C

ART UNIT	PAPER NUMBER
2626	

MAIL DATE	DELIVERY MODE
11/12/2008	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)
	10/706,282	BACHAR ET AL.
Office Action Summary	Examiner	Art Unit	
	MICHAEL C. COLUCCI	2626	

-- *The MAILING DATE of this communication appears on the cover sheet with the correspondence address* --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE <u>3</u> MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.
- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
  Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

1) ☐ Responsive to communication(s) filed on _____.

2a) ☒ This action is FINAL.   2b) ☐ This action is non-final.

3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

4) ☒ Claim(s) <u>1-45</u> is/are pending in the application.

    4a) Of the above claim(s) _____ is/are withdrawn from consideration.

5) ☐ Claim(s) _____ is/are allowed.

6) ☒ Claim(s) <u>1-45</u> is/are rejected.

7) ☐ Claim(s) _____ is/are objected to.

8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

9) ☐ The specification is objected to by the Examiner.

10) ☒ The drawing(s) filed on <u>13 November 2003</u> is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.

    Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

    Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

    a) ☐ All   b) ☐ Some * c) ☒ None of:

      1. ☐ Certified copies of the priority documents have been received.

      2. ☐ Certified copies of the priority documents have been received in Application No. _____.

      3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

    * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1) ☒ Notice of References Cited (PTO-892)

2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)

3) ☒ Information Disclosure Statement(s) (PTO/SB/08)
   Paper No(s)/Mail Date _____.

4) ☐ Interview Summary (PTO-413)
   Paper No(s)/Mail Date. _____.

5) ☐ Notice of Informal Patent Application

6) ☐ Other: _____.

DETAILED ACTION

Claim Rejections - 35 USC § 112

1.   The following is a quotation of the first paragraph of 35 U.S.C. 112:

> The specification shall contain a written description of the invention, and of the manner and process of making and using it, in such full, clear, concise, and exact terms as to enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to make and use the same and shall set forth the best mode contemplated by the inventor of carrying out his invention.

2.   Claim 42 is rejected under 35 U.S.C. 112, first paragraph, as failing to comply with the written description requirement. The claim(s) contains subject matter which was not described in the specification in such a way as to reasonably convey to one skilled in the relevant art that the inventor(s), at the time the application was filed, had possession of the claimed invention. Claim 42 cites "verifying that an agent requested a customer's permission to put the customer on hold" without any clear support in the specification.

Response to Arguments

3.   Applicants arguments with respect to claims 1, 19, and 34-45 have been considered but are moot in view of the new grounds of rejection. Eilbacher et al. US 6724887 B1 (hereinafter Eilbacher) has been incorporated to address analysis of a captured interaction within a time sequence/limit relative to a media type.

NOTE: In view of the present invention, Examiner would like to point out the definition of media as defined in the specification, wherein stated, "The media could be audio, video and other multi-media". Examiner therefore has maintained the use of Tsuchikawa; et

al. US 5748775 A (hereinafter Tsuchikawa) in view of Soundararajan US 20030106072

A1 (hereinafter Soundararajan), as both references incorporate the use of media and

media selection. Further Tsuchikawa teaches the capturing of time/temporal positions

of media (i.e. frames), wherein this method is functionally equivalent and equally

effective to a "pivot spot definer" as taught in the present invention.

Further, Examiner has incorporated Eilbacher to address interaction within a time

sequence, such as interaction captured between users or between a user and a service,

agent, or call handling system. Eilbacher teaches the capturing of interactions in a

media type environment. The combination of Tsuchikawa, Soundararajan, in view of

Eilbacher now addresses various forms of media and time based selection of captured

interactions.

Claim Rejections - 35 USC § 103

4.   The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all

obviousness rejections set forth in this Office action:

> (a) A patent may not be obtained though the invention is not identically disclosed or described as set
> forth in section 102 of this title, if the differences between the subject matter sought to be patented and
> the prior art are such that the subject matter as a whole would have been obvious at the time the
> invention was made to a person having ordinary skill in the art to which said subject matter pertains.
> Patentability shall not be negatived by the manner in which the invention was made.

5.   Claims 1-9, 11, 13, 16, 19-25, 31, 33-39, 41, 42, 44, and 45 are rejected under

35 U.S.C. 103(a) as being unpatentable over Tsuchikawa et al. US 5748775 A

(hereinafter Tsuchikawa) in view of Soundararajan US 20030106072 A1 (hereinafter

Soundararajan) and further in view of Eilbacher et al. US 6724887 B1 (hereinafter

Eilbacher).

Re claim 1, Tsuchikawa teaches an apparatus for event-driven content analysis

of a captured interaction, within a computerized system having a processing unit and a

storage unit (Col. 2 line 55 – Col. 3 line 13), the apparatus comprising the elements of:

a pivot spot definer component to mark an at least one time position in the

interaction media to indicate the occurrence of an at least one pre-defined event or data

item (Col. 5 lines 18-26);

a region of interest definer component to define a region of interest to determine

the time limits of an at least one segment of the interaction, the segment containing the

time position of the pivot spot (Col. 5 lines 27-51)

However, Tsuchikawa fails to teach a media type selector component to select a

type of an interaction media inputted for analysis from an at least one interaction

recording or storage device;

Soundararajan teaches a multimedia source input for receiving multimedia

content from a multimedia stream 102. The term "multimedia stream" as used herein is

intended to refer to signals that may originate from a cable, satellite, or terrestrial

broadcast, or from an alternative multiple-program stream. The multimedia content

preferably includes, but is not limited to, broadcast television video signals, such as

National Television Standards Committee (NTSC) signals, DTV signals, and high

definition television (HDTV) signals. The multimedia content may also include still

images, audio signals (e.g., from a satellite radio source), etc. The STB/DTV 104 may

include multiple multimedia inputs and a multiplexer or equivalent switching circuitry (not

shown) for selecting one of a plurality of multimedia sources (e.g., video camera, digital

still camera, etc.) (Soundararajan [0019]).

Therefore, it would have been obvious to one of ordinary skill in the art at the

time of the invention to modify the system of Tsuchikawato incorporate teach a media

type selector component to select a type of an interaction media inputted for analysis

from an at least one interaction recording or storage device as taught by Soundararajan

for the purposes of a universal control system fro various multimedia equipment/data,

wherein all multimedia can interface through a single distributed storage medium

(Soundararajan [0019]).

However, Tsuchikawa in view of Soundararajan fails to teach a captured

interaction

Eilbacher teaches a contact center 200 of FIG. 2, and in particular a telephone

call center. Referring to FIG. 3, customers 100 access the contact center through the

public switched telephone network (PSTN) 101 and an automatic call distribution

system 102 (PBX/ACD) directs the communication to one of a plurality of agent work

stations 104. Each agent work station 104 includes, for example, a computer and a

telephone set. Communications are directed to the agent stations 104 based on the

availability of the agent. In those contact centers handling communications for a

number of different clients, communications to a particular client may be routed to a

finite group of agents specifically trained to respond to the needs of that customer or

that client. Alternatively, the PBX/ACD 102 may include an interactive voice response

(IVR) system that presents an audio menu to a customer, requesting a response by way

of the customer's telephone key pad or by way of a voice response. Then, a call is

directed to a particular group of agent stations 104 or to a particular information retrieval

system, based on the responses of the customer. For example, the system can provide

the customer 100 with the address to which products should be returned or the Internet

address for obtaining additional product information. All data associated with the

customer's communication and the agents responsive interaction with the customer may

be recorded by a monitor module 210 within monitoring system 204. Examples of the

data typically recorded by a telephone call center system include the audio

communication between the customer and the agent, key pad data input by the

customer, screens viewed by the agent on the computer at the agent station 104

(carried by data line 105), the start and end time for the customer's communication, the

identity of the customer, including the originating telephone number and the called

number, the identity of the various agents servicing the communications, the length of

time the customer is on hold and the steps the customer navigated before terminating

the communication (Eilbacher Col. 8 lines 29-67).

Further, Eilbacher teaches incoming and outgoing calls can be recorded in their

entirety; particular calls can be identified for recording, such as by client or agent; and

calls can be recorded by event, such as calls exceeding five minutes. If "cradle-to-

grave" recording is used, then all information related to a particular telephone call or

caller-initiated transaction is recorded, from the time the call enters the contact center to

the later of: the caller hanging up or the agent completing the transaction. All of the interactions during the call are recorded, including interaction with the IVR system, time spent on hold, data keyed through the caller's key pad, conversations with the agent, and screens displayed by the agent at his/her station 104 during the transaction. These types of recordings allow for evaluation of the full customer experience throughout the transaction. As an example, the length of time a customer was on hold during a purchase transaction can be analyzed as a possible deterrent to completing a purchase. Such information may be used by contact center managers to modify their procedures, staffing, and/or equipment to improve the customer's experience when using the contact center. The comprehensiveness of the data capture of the present invention also allows for the subsequent verification of transaction content. For example, a dispute over what information was verbally provided by a caller applying for insurance coverage over the telephone can easily be resolved by replaying the application call in its entirety. Whether a customer selected size 10 can also be proven, as can whether the customer/investor authorized the purchase of 100 shares of a particular stock. (Eilbacher Col. 9 lines 10-39).

Furthermore, Eilbacher teaches types of parameters which can be analyzed by the customer experience analyzing unit 208 include the number of key strokes entered by the customer during a telephone call, the length of a telephone call, time on hold, number of transfers, or length of a queue. That is, if the length of the telephone call, the number of key strokes entered during the call or the length of a queue exceeded predetermined levels, the customer experience analyzing unit 208 can determine that

the communication was likely unsatisfactory. In addition, speech detection or word spotting can be used to detect certain inflammatory words such as curse words. For example, in the case of word spotting, an analysis is performed on recorded audio such as a telephone call. The audio is automatically processed, searching for any key words on a predefined list which have been identified as cause for concern. If any of the words are found, the call is marked as a potentially negative customer experience. This word spotting analysis can be done separately, or in addition to the stress analysis. Similarly, in connection with an e-mail communication, a text search can be used to look for words such as curse words, which might tend to indicate an unsatisfactory customer experience (Eilbacher Col. 11 lines 25-61).

Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to modify the system of Tsuchikawa in view of Soundararajan to incorporate event-driven content analysis of a captured interaction as taught by Eilbacher to allow for the monitoring of a customer and agent interaction, wherein various retrieval methods are implemented based on responses (Eilbacher Col. 8 lines 29-67) and key locations of media selected based on the customer responses (i.e. images, keywords, etc.) (Eilbacher Col. 11 lines 25-61).

Re claim 2, Tsuchikawa teaches the apparatus of claim 1 further comprising a content analysis input selector component to determine an at least one input or parameter for an at least one analyzer component (Col. 5 lines 5-17).

Re claim 3, Tsuchikawa teaches the apparatus of claim 1 further comprises an

analysis type selector component to identify and to select an at least one analyzer

component type for determining the Region of Interest (Col. 5 lines 27-51).

Re claim 4, Tsuchikawa teaches the apparatus of claim 1 further comprising an

audio analyzer component for performing an analysis on the media selected by the

media selector component in a location adjacent to the pivot spot identified by the pivot

spot defined component (Col. 5 lines 5-17).

However, Tsuchikawa fails to teach a media selector component (Soundararajan

[0019]);

Soundararajan teaches a multimedia source input for receiving multimedia

content from a multimedia stream 102. The term "multimedia stream" as used herein is

intended to refer to signals that may originate from a cable, satellite, or terrestrial

broadcast, or from an alternative multiple-program stream. The multimedia content

preferably includes, but is not limited to, broadcast television video signals, such as

National Television Standards Committee (NTSC) signals, DTV signals, and high

definition television (HDTV) signals. The multimedia content may also include still

images, audio signals (e.g., from a satellite radio source), etc. The STB/DTV 104 may

include multiple multimedia inputs and a multiplexer or equivalent switching circuitry (not

shown) for selecting one of a plurality of multimedia sources (e.g., video camera, digital

still camera, etc.).

Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to modify the system of Tsuchikawato incorporate a media type selector to select a type of interaction media inputted for analysis on a frame by frame basis as taught by Soundararajan for the purposes of a universal control system fro various multimedia equipment/data, wherein all multimedia can interface through a single distributed storage medium (Soundararajan [0019]).

Re claim 5, Tsuchikawa teaches the apparatus of claim 1 further comprising an analyzer component for performing an analysis on the media selected by the media selector component in a location adjacent to the pivot spot identified by the pivot spot definer component (Col. 5 lines 5-17) using an analyzer selected by the analysis type selector using parameters fed to, or selected by the content analysis input selector component (Col. 5 lines 27-51).

However, Tsuchikawa fails to teach a media selector component (Soundararajan [0019]);

Soundararajan teaches a multimedia source input for receiving multimedia content from a multimedia stream 102. The term "multimedia stream" as used herein is intended to refer to signals that may originate from a cable, satellite, or terrestrial broadcast, or from an alternative multiple-program stream. The multimedia content preferably includes, but is not limited to, broadcast television video signals, such as National Television Standards Committee (NTSC) signals, DTV signals, and high definition television (HDTV) signals. The multimedia content may also include still

images, audio signals (e.g., from a satellite radio source), etc. The STB/DTV 104 may

include multiple multimedia inputs and a multiplexer or equivalent switching circuitry (not

shown) for selecting one of a plurality of multimedia sources (e.g., video camera, digital

still camera, etc.).

Therefore, it would have been obvious to one of ordinary skill in the art at the

time of the invention to modify the system of Tsuchikawa to incorporate a media type

selector to select a type of interaction media inputted for analysis on a frame by frame

basis as taught by Soundararajan for the purposes of a universal control system fro

various multimedia equipment/data, wherein all multimedia can interface through a

single distributed storage medium (Soundararajan [0019]).

Re claim 6, Tsuchikawa teaches the apparatus of claim 1 further comprising an

analyzer component for performing an analysis on the media selected by the media

selector component within the region of interest identified by the region of interest

definer component (Col. 5 lines 27-51) using an analyzer selected by the analysis type

selector using parameters fed to (Col. 5 lines 5-17), or selected by the content analysis

input selector component

However, Tsuchikawa fails to teach a media selector component (Soundararajan

[0019]);

Soundararajan teaches a multimedia source input for receiving multimedia

content from a multimedia stream 102. The term "multimedia stream" as used herein is

intended to refer to signals that may originate from a cable, satellite, or terrestrial

broadcast, or from an alternative multiple-program stream. The multimedia content

preferably includes, but is not limited to, broadcast television video signals, such as

National Television Standards Committee (NTSC) signals, DTV signals, and high

definition television (HDTV) signals. The multimedia content may also include still

images, audio signals (e.g., from a satellite radio source), etc. The STB/DTV 104 may

include multiple multimedia inputs and a multiplexer or equivalent switching circuitry (not

shown) for selecting one of a plurality of multimedia sources (e.g., video camera, digital

still camera, etc.).

   Therefore, it would have been obvious to one of ordinary skill in the art at the

time of the invention to modify the system of Tsuchikawato incorporate a media type

selector to select a type of interaction media inputted for analysis on a frame by frame

basis as taught by Soundararajan for the purposes of a universal control system fro

various multimedia equipment/data, wherein all multimedia can interface through a

single distributed storage medium (Soundararajan [0019]).

   Re claims 7 and 31, Tsuchikawa teaches the apparatus of claim 1 wherein the

region of interest defined by the region of interest definer component further comprises

an optimization component for optimizing the region of interest (Col. 5 lines 27-51 & Fig.

3 item 200)

Re claim 8, Tsuchikawa teaches an apparatus of claim 1 further comprises a
content analysis inputs table to hold in storage the at least one selectable input values
(Col. 5 lines 5-17).

Re claim 9, Tsuchikawa teaches the apparatus of claim 1 further comprises the
element of an audio analyzer component to analyze the audio elements of the
interaction data (Col. 5 lines 5-17).

Re claim 11, Tsuchikawa teaches the apparatus of claim 1 further comprises a
screen event analyzer component to identify and capture an at least one screen and an
at least one screen event associated with the interaction data and capture at least one
screen based on the screen event (Col. 5 lines 5-17 & Fig. 4).

Re claim 13, Tsuchikawa teaches the apparatus of claim 1 further comprising an
analysis module for performing an analysis on the media (Col. 5 lines 5-17 & Fig. 4).

Re claim 16, Tsuchikawa teaches the apparatus of claim 1 wherein the region of
interest is a specific segment of the interaction media that is analyzed to extract
meaningful interaction-specific information in an organization (Col. 5 lines 27-51).

Re claim 20, Tsuchikawa fails to teach selecting an interaction media to analyze
(Soundararajan [0019]);

Soundararajan teaches a multimedia source input for receiving multimedia

content from a multimedia stream 102. The term "multimedia stream" as used herein is

intended to refer to signals that may originate from a cable, satellite, or terrestrial

broadcast, or from an alternative multiple-program stream. The multimedia content

preferably includes, but is not limited to, broadcast television video signals, such as

National Television Standards Committee (NTSC) signals, DTV signals, and high

definition television (HDTV) signals. The multimedia content may also include still

images, audio signals (e.g., from a satellite radio source), etc. The STB/DTV 104 may

include multiple multimedia inputs and a multiplexer or equivalent switching circuitry (not

shown) for selecting one of a plurality of multimedia sources (e.g., video camera, digital

still camera, etc.).

Therefore, it would have been obvious to one of ordinary skill in the art at the

time of the invention to modify the system of Tsuchikawato incorporate selecting an

interaction media to analyze as taught by Soundararajan for the purposes of a universal

control system fro various multimedia equipment/data, wherein all multimedia can

interface through a single distributed storage medium (Soundararajan [0019]).

Re claim 21, Tsuchikawa teaches the method of claim 19 further comprising the

step of selecting a method for the analysis of the at least one interaction media based

on the at least one event associated with the interaction (Fig. 3).

Re claim 22, Tsuchikawa teaches the method of claim 19 further comprising the

step of selecting a method for the analysis of the at least one interaction media based

on the result of a previously performed analysis (Fig. 6 item 130)

Re claim 23, Tsuchikawa teaches the method of claim 19 further comprising the

step of selecting the parameters to be used in the at least one analysis instruction step

on the at least one segment of the interaction media (Col. 5 lines 5-17).

Re claim 24, Tsuchikawa teaches the method of claim 19 further comprising the

step of optimizing the region of interest by performing an at least one analysis

instruction step within the region of interest (Col. 5 lines 27-51) and readjusting the

region of interest in accordance with the results of the at least one analysis instruction

step (Fig. 3).

Re claim 25, Tsuchikawa teaches the method of claim 19 wherein the region of

interest is predetermined by a user or an apparatus (Col. 5 lines 27-51).

Re claim 33, Tsuchikawa teaches the method of claim 19 further comprising the

step of adjusting the at least one pivot spot (Fig. 4) or region of interest on the

interaction media (Col. 5 lines 27-51).

Re claims 19, 44, and 45, Tsuchikawa teaches a method for event-driven content analysis, within a computerized system having a processing unit and a storage unit, the method comprising the steps of:

determining an at least one pivot spot, being a time position, on an interaction media associated with an at least one event associated with the interaction (Col. 5 lines 18-26);

determining the time limits of the at least one segment of the interaction media to be analyzed, said limits defining an initial region of interest within the interaction (Col. 5 lines 27-51);

optimizing the initial region of interest by performing an at least one analysis instruction step within the initial region of interest and readjusting the initial region of interest in accordance with a result of the at least one analysis instruction step, to obtain a region of interest (Col. 5 lines 27-51, and Fig. 3 item 200);

However, Tsuchikawa fails to teach selecting a first method for the analysis of the at least one interaction media based on the at least one event associated with the interaction;

selecting a second method for analyzing the region of interest; an

analyzing the region of interest using the second method

Soundararajan teaches a multimedia source input for receiving multimedia content from a multimedia stream 102. The term "multimedia stream" as used herein is intended to refer to signals that may originate from a cable, satellite, or terrestrial

broadcast, or from an alternative multiple-program stream. The multimedia content

preferably includes, but is not limited to, broadcast television video signals, such as

National Television Standards Committee (NTSC) signals, DTV signals, and high

definition television (HDTV) signals. The multimedia content may also include still

images, audio signals (e.g., from a satellite radio source), etc. The STB/DTV 104 may

include multiple multimedia inputs and a multiplexer or equivalent switching circuitry (not

shown) for selecting one of a plurality of multimedia sources (e.g., video camera, digital

still camera, etc.) (Soundararajan [0019]).

Therefore, it would have been obvious to one of ordinary skill in the art at the

time of the invention to modify the system of Tsuchikawato incorporate selecting a first

method for the analysis of the at least one interaction media based on the at least one

event associated with the interaction, selecting a second method for analyzing the

region of interest, and analyzing the region of interest using the second method a media

type selector component to select a type of an interaction media inputted for analysis

from an at least one interaction recording or storage device as taught by Soundararajan

for the purposes of a universal control system fro various multimedia equipment/data,

wherein all multimedia can interface through a single distributed storage medium

(Soundararajan [0019]).

However, Tsuchikawa in view of Soundararajan fails to teach interaction media

receiving interaction data and associated meta-data from an at least one

interaction;

readjusting the initial region of interest in accordance with a result of the at least one analysis instruction step, to obtain a region of interest.

Eilbacher teaches a contact center 200 of FIG. 2, and in particular a telephone call center. Referring to FIG. 3, customers 100 access the contact center through the public switched telephone network (PSTN) 101 and an automatic call distribution system 102 (PBX/ACD) directs the communication to one of a plurality of agent work stations 104. Each agent work station 104 includes, for example, a computer and a telephone set. Communications are directed to the agent stations 104 based on the availability of the agent. In those contact centers handling communications for a number of different clients, communications to a particular client may be routed to a finite group of agents specifically trained to respond to the needs of that customer or that client. Alternatively, the PBX/ACD 102 may include an interactive voice response (IVR) system that presents an audio menu to a customer, requesting a response by way of the customer's telephone key pad or by way of a voice response. Then, a call is directed to a particular group of agent stations 104 or to a particular information retrieval system, based on the responses of the customer. For example, the system can provide the customer 100 with the address to which products should be returned or the Internet address for obtaining additional product information. All data associated with the customer's communication and the agents responsive interaction with the customer may be recorded by a monitor module 210 within monitoring system 204. Examples of the data typically recorded by a telephone call center system include the audio communication between the customer and the agent, key pad data input by the

customer, screens viewed by the agent on the computer at the agent station 104

(carried by data line 105), the start and end time for the customer's communication, the

identity of the customer, including the originating telephone number and the called

number, the identity of the various agents servicing the communications, the length of

time the customer is on hold and the steps the customer navigated before terminating

the communication (Eilbacher Col. 8 lines 29-67).

Further, Eilbacher teaches incoming and outgoing calls can be recorded in their

entirety; particular calls can be identified for recording, such as by client or agent; and

calls can be recorded by event, such as calls exceeding five minutes. If "cradle-to-

grave" recording is used, then all information related to a particular telephone call or

caller-initiated transaction is recorded, from the time the call enters the contact center to

the later of: the caller hanging up or the agent completing the transaction. All of the

interactions during the call are recorded, including interaction with the IVR system, time

spent on hold, data keyed through the caller's key pad, conversations with the agent,

and screens displayed by the agent at his/her station 104 during the transaction. These

types of recordings allow for evaluation of the full customer experience throughout the

transaction. As an example, the length of time a customer was on hold during a

purchase transaction can be analyzed as a possible deterrent to completing a purchase.

Such information may be used by contact center managers to modify their procedures,

staffing, and/or equipment to improve the customer's experience when using the contact

center. The comprehensiveness of the data capture of the present invention also allows

for the subsequent verification of transaction content. For example, a dispute over what

information was verbally provided by a caller applying for insurance coverage over the
telephone can easily be resolved by replaying the application call in its entirety.
Whether a customer selected size 10 can also be proven, as can whether the
customer/investor authorized the purchase of 100 shares of a particular stock.
(Eilbacher Col. 9 lines 10-39).

Furthermore, Eilbacher teaches types of parameters which can be analyzed by
the customer experience analyzing unit 208 include the number of key strokes entered
by the customer during a telephone call, the length of a telephone call, time on hold,
number of transfers, or length of a queue. That is, if the length of the telephone call, the
number of key strokes entered during the call or the length of a queue exceeded
predetermined levels, the customer experience analyzing unit 208 can determine that
the communication was likely unsatisfactory. In addition, speech detection or word
spotting can be used to detect certain inflammatory words such as curse words. For
example, in the case of word spotting, an analysis is performed on recorded audio such
as a telephone call. The audio is automatically processed, searching for any key words
on a predefined list which have been identified as cause for concern. If any of the
words are found, the call is marked as a potentially negative customer experience. This
word spotting analysis can be done separately, or in addition to the stress analysis.
Similarly, in connection with an e-mail communication, a text search can be used to look
for words such as curse words, which might tend to indicate an unsatisfactory customer
experience (Eilbacher Col. 11 lines 25-61).

Therefore, it would have been obvious to one of ordinary skill in the art at the

time of the invention to modify the system of Tsuchikawa in view of Soundararajan to

incorporate interaction media receiving interaction data and associated meta-data from

an at least one interaction and readjusting the initial region of interest in accordance

with a result of the at least one analysis instruction step, to obtain a region of interest as

taught by Eilbacher to allow for the monitoring of a customer and agent interaction,

wherein various retrieval methods are implemented based on responses (Eilbacher Col.

8 lines 29-67) and key locations of media selected based on the customer responses

(i.e. images, keywords, etc.) to create and ideal/optimal retrieval of information

(Eilbacher Col. 11 lines 25-61).

Re claims 34 and 35, Tsuchikawa in view of Soundararajan fails to teach the

apparatus of claim 1 wherein the pivot spot is determined using at least one item

selected from the group consisting of: a Computer Telephony Integration event; a

screen event; an emotional level; and a spotted word.

Eilbacher teaches a contact center 200 of FIG. 2, and in particular a telephone

call center. Referring to FIG. 3, customers 100 access the contact center through the

public switched telephone network (PSTN) 101 and an automatic call distribution

system 102 (PBX/ACD) directs the communication to one of a plurality of agent work

stations 104. Each agent work station 104 includes, for example, a computer and a

telephone set. Communications are directed to the agent stations 104 based on the

availability of the agent. In those contact centers handling communications for a

number of different clients, communications to a particular client may be routed to a

finite group of agents specifically trained to respond to the needs of that customer or

that client. Alternatively, the PBX/ACD 102 may include an interactive voice response

(IVR) system that presents an audio menu to a customer, requesting a response by way

of the customer's telephone key pad or by way of a voice response. Then, a call is

directed to a particular group of agent stations 104 or to a particular information retrieval

system, based on the responses of the customer. For example, the system can provide

the customer 100 with the address to which products should be returned or the Internet

address for obtaining additional product information. All data associated with the

customer's communication and the agents responsive interaction with the customer may

be recorded by a monitor module 210 within monitoring system 204. Examples of the

data typically recorded by a telephone call center system include the audio

communication between the customer and the agent, key pad data input by the

customer, screens viewed by the agent on the computer at the agent station 104

(carried by data line 105), the start and end time for the customer's communication, the

identity of the customer, including the originating telephone number and the called

number, the identity of the various agents servicing the communications, the length of

time the customer is on hold and the steps the customer navigated before terminating

the communication (Eilbacher Col. 8 lines 29-67).

Further, Eilbacher teaches incoming and outgoing calls can be recorded in their

entirety; particular calls can be identified for recording, such as by client or agent; and

calls can be recorded by event, such as calls exceeding five minutes. If "cradle-to-

grave" recording is used, then all information related to a particular telephone call or caller-initiated transaction is recorded, from the time the call enters the contact center to the later of: the caller hanging up or the agent completing the transaction. All of the interactions during the call are recorded, including interaction with the IVR system, time spent on hold, data keyed through the caller's key pad, conversations with the agent, and screens displayed by the agent at his/her station 104 during the transaction. These types of recordings allow for evaluation of the full customer experience throughout the transaction. As an example, the length of time a customer was on hold during a purchase transaction can be analyzed as a possible deterrent to completing a purchase. Such information may be used by contact center managers to modify their procedures, staffing, and/or equipment to improve the customer's experience when using the contact center. The comprehensiveness of the data capture of the present invention also allows for the subsequent verification of transaction content. For example, a dispute over what information was verbally provided by a caller applying for insurance coverage over the telephone can easily be resolved by replaying the application call in its entirety. Whether a customer selected size 10 can also be proven, as can whether the customer/investor authorized the purchase of 100 shares of a particular stock. (Eilbacher Col. 9 lines 10-39).

Furthermore, Eilbacher teaches types of parameters which can be analyzed by the customer experience analyzing unit 208 include the number of key strokes entered by the customer during a telephone call, the length of a telephone call, time on hold, number of transfers, or length of a queue. That is, if the length of the telephone call, the

number of key strokes entered during the call or the length of a queue exceeded

predetermined levels, the customer experience analyzing unit 208 can determine that

the communication was likely unsatisfactory. In addition, speech detection or word

spotting can be used to detect certain inflammatory words such as curse words. For

example, in the case of word spotting, an analysis is performed on recorded audio such

as a telephone call. The audio is automatically processed, searching for any key words

on a predefined list which have been identified as cause for concern. If any of the

words are found, the call is marked as a potentially negative customer experience. This

word spotting analysis can be done separately, or in addition to the stress analysis.

Similarly, in connection with an e-mail communication, a text search can be used to look

for words such as curse words, which might tend to indicate an unsatisfactory customer

experience (Eilbacher Col. 11 lines 25-61).

Therefore, it would have been obvious to one of ordinary skill in the art at the

time of the invention to modify the system of Tsuchikawa in view of Soundararajan to

incorporate the pivot spot is determined using at least one item selected from the group

consisting of: a Computer Telephony Integration event; a screen event; an emotional

level; and a spotted word as taught by Eilbacher to allow for the monitoring of a

customer and agent interaction, wherein various retrieval methods are implemented

based on responses (Eilbacher Col. 8 lines 29-67) and key locations of media selected

based on the customer responses (i.e. images, keywords, etc.) to create and

ideal/optimal retrieval of information (Eilbacher Col. 11 lines 25-61).

Re claims 36 and 37, Tsuchikawa in view of Soundararajan fails to teach the apparatus of claim 1 wherein optimizing the region of interest is set according to a predetermined length, speaker separation, audio analysis, event analysis, a Computer Telephony Integration event analysis, CRM event analysis, a screen event; an emotional level, or a spotted word.

Eilbacher teaches a contact center 200 of FIG. 2, and in particular a telephone call center. Referring to FIG. 3, customers 100 access the contact center through the public switched telephone network (PSTN) 101 and an automatic call distribution system 102 (PBX/ACD) directs the communication to one of a plurality of agent work stations 104. Each agent work station 104 includes, for example, a computer and a telephone set. Communications are directed to the agent stations 104 based on the availability of the agent. In those contact centers handling communications for a number of different clients, communications to a particular client may be routed to a finite group of agents specifically trained to respond to the needs of that customer or that client. Alternatively, the PBX/ACD 102 may include an interactive voice response (IVR) system that presents an audio menu to a customer, requesting a response by way of the customer's telephone key pad or by way of a voice response. Then, a call is directed to a particular group of agent stations 104 or to a particular information retrieval system, based on the responses of the customer. For example, the system can provide the customer 100 with the address to which products should be returned or the Internet address for obtaining additional product information. All data associated with the customer's communication and the agents responsive interaction with the customer may

be recorded by a monitor module 210 within monitoring system 204. Examples of the

data typically recorded by a telephone call center system include the audio

communication between the customer and the agent, key pad data input by the

customer, screens viewed by the agent on the computer at the agent station 104

(carried by data line 105), the start and end time for the customer's communication, the

identity of the customer, including the originating telephone number and the called

number, the identity of the various agents servicing the communications, the length of

time the customer is on hold and the steps the customer navigated before terminating

the communication (Eilbacher Col. 8 lines 29-67).

Further, Eilbacher teaches incoming and outgoing calls can be recorded in their

entirety; particular calls can be identified for recording, such as by client or agent; and

calls can be recorded by event, such as calls exceeding five minutes. If "cradle-to-

grave" recording is used, then all information related to a particular telephone call or

caller-initiated transaction is recorded, from the time the call enters the contact center to

the later of: the caller hanging up or the agent completing the transaction. All of the

interactions during the call are recorded, including interaction with the IVR system, time

spent on hold, data keyed through the caller's key pad, conversations with the agent,

and screens displayed by the agent at his/her station 104 during the transaction. These

types of recordings allow for evaluation of the full customer experience throughout the

transaction. As an example, the length of time a customer was on hold during a

purchase transaction can be analyzed as a possible deterrent to completing a purchase.

Such information may be used by contact center managers to modify their procedures,

staffing, and/or equipment to improve the customer's experience when using the contact

center. The comprehensiveness of the data capture of the present invention also allows

for the subsequent verification of transaction content. For example, a dispute over what

information was verbally provided by a caller applying for insurance coverage over the

telephone can easily be resolved by replaying the application call in its entirety.

Whether a customer selected size 10 can also be proven, as can whether the

customer/investor authorized the purchase of 100 shares of a particular stock.

(Eilbacher Col. 9 lines 10-39).

Furthermore, Eilbacher teaches types of parameters which can be analyzed by

the customer experience analyzing unit 208 include the number of key strokes entered

by the customer during a telephone call, the length of a telephone call, time on hold,

number of transfers, or length of a queue. That is, if the length of the telephone call, the

number of key strokes entered during the call or the length of a queue exceeded

predetermined levels, the customer experience analyzing unit 208 can determine that

the communication was likely unsatisfactory. In addition, speech detection or word

spotting can be used to detect certain inflammatory words such as curse words. For

example, in the case of word spotting, an analysis is performed on recorded audio such

as a telephone call. The audio is automatically processed, searching for any key words

on a predefined list which have been identified as cause for concern. If any of the

words are found, the call is marked as a potentially negative customer experience. This

word spotting analysis can be done separately, or in addition to the stress analysis.

Similarly, in connection with an e-mail communication, a text search can be used to look

for words such as curse words, which might tend to indicate an unsatisfactory customer

experience (Eilbacher Col. 11 lines 25-61).

Therefore, it would have been obvious to one of ordinary skill in the art at the

time of the invention to modify the system of Tsuchikawa in view of Soundararajan to

incorporate optimizing the region of interest is set according to a predetermined length,

speaker separation, audio analysis, event analysis, a Computer Telephony Integration

event analysis, CRM event analysis, a screen event; an emotional level, or a spotted

word as taught by Eilbacher to allow for the monitoring of a customer and agent

interaction, wherein various retrieval methods are implemented based on responses

(Eilbacher Col. 8 lines 29-67) and key locations of media selected based on the

customer responses (i.e. images, keywords, etc.) to create and ideal/optimal retrieval of

information (Eilbacher Col. 11 lines 25-61).

Re claims 38 and 39, Tsuchikawa in view of Soundararajan fails to teach the

apparatus of claim 1 wherein the captured interaction is between an agent and a

customer.

Eilbacher teaches a contact center 200 of FIG. 2, and in particular a telephone

call center. Referring to FIG. 3, customers 100 access the contact center through the

public switched telephone network (PSTN) 101 and an automatic call distribution

system 102 (PBX/ACD) directs the communication to one of a plurality of agent work

stations 104. Each agent work station 104 includes, for example, a computer and a

telephone set. Communications are directed to the agent stations 104 based on the

availability of the agent. In those contact centers handling communications for a

number of different clients, communications to a particular client may be routed to a

finite group of agents specifically trained to respond to the needs of that customer or

that client. Alternatively, the PBX/ACD 102 may include an interactive voice response

(IVR) system that presents an audio menu to a customer, requesting a response by way

of the customer's telephone key pad or by way of a voice response. Then, a call is

directed to a particular group of agent stations 104 or to a particular information retrieval

system, based on the responses of the customer. For example, the system can provide

the customer 100 with the address to which products should be returned or the Internet

address for obtaining additional product information. All data associated with the

customer's communication and the agents responsive interaction with the customer may

be recorded by a monitor module 210 within monitoring system 204. Examples of the

data typically recorded by a telephone call center system include the audio

communication between the customer and the agent, key pad data input by the

customer, screens viewed by the agent on the computer at the agent station 104

(carried by data line 105), the start and end time for the customer's communication, the

identity of the customer, including the originating telephone number and the called

number, the identity of the various agents servicing the communications, the length of

time the customer is on hold and the steps the customer navigated before terminating

the communication (Eilbacher Col. 8 lines 29-67).

      Further, Eilbacher teaches incoming and outgoing calls can be recorded in their

entirety; particular calls can be identified for recording, such as by client or agent; and

calls can be recorded by event, such as calls exceeding five minutes. If "cradle-to-grave" recording is used, then all information related to a particular telephone call or caller-initiated transaction is recorded, from the time the call enters the contact center to the later of: the caller hanging up or the agent completing the transaction. All of the interactions during the call are recorded, including interaction with the IVR system, time spent on hold, data keyed through the caller's key pad, conversations with the agent, and screens displayed by the agent at his/her station 104 during the transaction. These types of recordings allow for evaluation of the full customer experience throughout the transaction. As an example, the length of time a customer was on hold during a purchase transaction can be analyzed as a possible deterrent to completing a purchase. Such information may be used by contact center managers to modify their procedures, staffing, and/or equipment to improve the customer's experience when using the contact center. The comprehensiveness of the data capture of the present invention also allows for the subsequent verification of transaction content. For example, a dispute over what information was verbally provided by a caller applying for insurance coverage over the telephone can easily be resolved by replaying the application call in its entirety. Whether a customer selected size 10 can also be proven, as can whether the customer/investor authorized the purchase of 100 shares of a particular stock. (Eilbacher Col. 9 lines 10-39).

Furthermore, Eilbacher teaches types of parameters which can be analyzed by the customer experience analyzing unit 208 include the number of key strokes entered by the customer during a telephone call, the length of a telephone call, time on hold,

number of transfers, or length of a queue. That is, if the length of the telephone call, the number of key strokes entered during the call or the length of a queue exceeded predetermined levels, the customer experience analyzing unit 208 can determine that the communication was likely unsatisfactory. In addition, speech detection or word spotting can be used to detect certain inflammatory words such as curse words. For example, in the case of word spotting, an analysis is performed on recorded audio such as a telephone call. The audio is automatically processed, searching for any key words on a predefined list which have been identified as cause for concern. If any of the words are found, the call is marked as a potentially negative customer experience. This word spotting analysis can be done separately, or in addition to the stress analysis. Similarly, in connection with an e-mail communication, a text search can be used to look for words such as curse words, which might tend to indicate an unsatisfactory customer experience (Eilbacher Col. 11 lines 25-61).

Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to modify the system of Tsuchikawa in view of Soundararajan to incorporate the captured interaction is between an agent and a customer as taught by Eilbacher to allow for the monitoring of a customer and agent interaction, wherein various retrieval methods are implemented based on responses (Eilbacher Col. 8 lines 29-67) and key locations of media selected based on the customer responses (i.e. images, keywords, etc.) to create and ideal/optimal retrieval of information (Eilbacher Col. 11 lines 25-61).

Re claim 41, Tsuchikawa in view of Soundararajan fails to teach the method of

claim 19 wherein the method is used for detecting customer churn indications, wherein

the pivot spot is defined using a CTI hold event or a cancellation-related screen event;

and wherein the region of interest is defined using emotion analysis or word spotting.

Eilbacher teaches a contact center 200 of FIG. 2, and in particular a telephone

call center. Referring to FIG. 3, customers 100 access the contact center through the

public switched telephone network (PSTN) 101 and an automatic call distribution

system 102 (PBX/ACD) directs the communication to one of a plurality of agent work

stations 104. Each agent work station 104 includes, for example, a computer and a

telephone set. Communications are directed to the agent stations 104 based on the

availability of the agent. In those contact centers handling communications for a

number of different clients, communications to a particular client may be routed to a

finite group of agents specifically trained to respond to the needs of that customer or

that client. Alternatively, the PBX/ACD 102 may include an interactive voice response

(IVR) system that presents an audio menu to a customer, requesting a response by way

of the customer's telephone key pad or by way of a voice response. Then, a call is

directed to a particular group of agent stations 104 or to a particular information retrieval

system, based on the responses of the customer. For example, the system can provide

the customer 100 with the address to which products should be returned or the Internet

address for obtaining additional product information. All data associated with the

customer's communication and the agents responsive interaction with the customer may

be recorded by a monitor module 210 within monitoring system 204. Examples of the

data typically recorded by a telephone call center system include the audio

communication between the customer and the agent, key pad data input by the

customer, screens viewed by the agent on the computer at the agent station 104

(carried by data line 105), the start and end time for the customer's communication, the

identity of the customer, including the originating telephone number and the called

number, the identity of the various agents servicing the communications, the length of

time the customer is on hold and the steps the customer navigated before terminating

the communication (Eilbacher Col. 8 lines 29-67).

Further, Eilbacher teaches incoming and outgoing calls can be recorded in their

entirety; particular calls can be identified for recording, such as by client or agent; and

calls can be recorded by event, such as calls exceeding five minutes. If "cradle-to-

grave" recording is used, then all information related to a particular telephone call or

caller-initiated transaction is recorded, from the time the call enters the contact center to

the later of: the caller hanging up or the agent completing the transaction. All of the

interactions during the call are recorded, including interaction with the IVR system, time

spent on hold, data keyed through the caller's key pad, conversations with the agent,

and screens displayed by the agent at his/her station 104 during the transaction. These

types of recordings allow for evaluation of the full customer experience throughout the

transaction. As an example, the length of time a customer was on hold during a

purchase transaction can be analyzed as a possible deterrent to completing a purchase.

Such information may be used by contact center managers to modify their procedures,

staffing, and/or equipment to improve the customer's experience when using the contact

center. The comprehensiveness of the data capture of the present invention also allows

for the subsequent verification of transaction content. For example, a dispute over what

information was verbally provided by a caller applying for insurance coverage over the

telephone can easily be resolved by replaying the application call in its entirety.

Whether a customer selected size 10 can also be proven, as can whether the

customer/investor authorized the purchase of 100 shares of a particular stock.

(Eilbacher Col. 9 lines 10-39).

Furthermore, Eilbacher teaches types of parameters which can be analyzed by

the customer experience analyzing unit 208 include the number of key strokes entered

by the customer during a telephone call, the length of a telephone call, time on hold,

number of transfers, or length of a queue. That is, if the length of the telephone call, the

number of key strokes entered during the call or the length of a queue exceeded

predetermined levels, the customer experience analyzing unit 208 can determine that

the communication was likely unsatisfactory. In addition, speech detection or word

spotting can be used to detect certain inflammatory words such as curse words. For

example, in the case of word spotting, an analysis is performed on recorded audio such

as a telephone call. The audio is automatically processed, searching for any key words

on a predefined list which have been identified as cause for concern. If any of the

words are found, the call is marked as a potentially negative customer experience. This

word spotting analysis can be done separately, or in addition to the stress analysis.

Similarly, in connection with an e-mail communication, a text search can be used to look

for words such as curse words, which might tend to indicate an unsatisfactory customer experience (Eilbacher Col. 11 lines 25-61).

Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to modify the system of Tsuchikawa in view of Soundararajan to incorporate detecting customer churn indications, wherein the pivot spot is defined using a CTI hold event or a cancellation-related screen event; and wherein the region of interest is defined using emotion analysis or word spotting as taught by Eilbacher to allow for the monitoring of a customer and agent interaction, wherein various retrieval methods are implemented based on responses (Eilbacher Col. 8 lines 29-67) and key locations of media selected based on the customer responses (i.e. images, keywords, etc.) to create and ideal/optimal retrieval of information (Eilbacher Col. 11 lines 25-61).

Re claim 42, Tsuchikawa in view of Soundararajan fails to teach the method of claim 19 wherein the method is used for verifying that an agent requested a customer's permission to put the customer on hold, wherein the pivot spot is the time the agent put the customer on hold, the initial region of interest is the whole interaction, and wherein the region of interest is defined by a first predetermined number of seconds prior to the pivot spot and a second predetermined number of seconds following the hold.

Eilbacher teaches a contact center 200 of FIG. 2, and in particular a telephone call center. Referring to FIG. 3, customers 100 access the contact center through the public switched telephone network (PSTN) 101 and an automatic call distribution system 102 (PBX/ACD) directs the communication to one of a plurality of agent work

stations 104. Each agent work station 104 includes, for example, a computer and a

telephone set. Communications are directed to the agent stations 104 based on the

availability of the agent. In those contact centers handling communications for a

number of different clients, communications to a particular client may be routed to a

finite group of agents specifically trained to respond to the needs of that customer or

that client. Alternatively, the PBX/ACD 102 may include an interactive voice response

(IVR) system that presents an audio menu to a customer, requesting a response by way

of the customer's telephone key pad or by way of a voice response. Then, a call is

directed to a particular group of agent stations 104 or to a particular information retrieval

system, based on the responses of the customer. For example, the system can provide

the customer 100 with the address to which products should be returned or the Internet

address for obtaining additional product information. All data associated with the

customer's communication and the agents responsive interaction with the customer may

be recorded by a monitor module 210 within monitoring system 204. Examples of the

data typically recorded by a telephone call center system include the audio

communication between the customer and the agent, key pad data input by the

customer, screens viewed by the agent on the computer at the agent station 104

(carried by data line 105), the start and end time for the customer's communication, the

identity of the customer, including the originating telephone number and the called

number, the identity of the various agents servicing the communications, the length of

time the customer is on hold and the steps the customer navigated before terminating

the communication (Eilbacher Col. 8 lines 29-67).

Further, Eilbacher teaches incoming and outgoing calls can be recorded in their entirety; particular calls can be identified for recording, such as by client or agent; and calls can be recorded by event, such as calls exceeding five minutes. If "cradle-to-grave" recording is used, then all information related to a particular telephone call or caller-initiated transaction is recorded, from the time the call enters the contact center to the later of: the caller hanging up or the agent completing the transaction. All of the interactions during the call are recorded, including interaction with the IVR system, time spent on hold, data keyed through the caller's key pad, conversations with the agent, and screens displayed by the agent at his/her station 104 during the transaction. These types of recordings allow for evaluation of the full customer experience throughout the transaction. As an example, the length of time a customer was on hold during a purchase transaction can be analyzed as a possible deterrent to completing a purchase. Such information may be used by contact center managers to modify their procedures, staffing, and/or equipment to improve the customer's experience when using the contact center. The comprehensiveness of the data capture of the present invention also allows for the subsequent verification of transaction content. For example, a dispute over what information was verbally provided by a caller applying for insurance coverage over the telephone can easily be resolved by replaying the application call in its entirety. Whether a customer selected size 10 can also be proven, as can whether the customer/investor authorized the purchase of 100 shares of a particular stock. (Eilbacher Col. 9 lines 10-39).

Furthermore, Eilbacher teaches types of parameters which can be analyzed by

the customer experience analyzing unit 208 include the number of key strokes entered

by the customer during a telephone call, the length of a telephone call, time on hold,

number of transfers, or length of a queue. That is, if the length of the telephone call, the

number of key strokes entered during the call or the length of a queue exceeded

predetermined levels, the customer experience analyzing unit 208 can determine that

the communication was likely unsatisfactory. In addition, speech detection or word

spotting can be used to detect certain inflammatory words such as curse words. For

example, in the case of word spotting, an analysis is performed on recorded audio such

as a telephone call. The audio is automatically processed, searching for any key words

on a predefined list which have been identified as cause for concern. If any of the

words are found, the call is marked as a potentially negative customer experience. This

word spotting analysis can be done separately, or in addition to the stress analysis.

Similarly, in connection with an e-mail communication, a text search can be used to look

for words such as curse words, which might tend to indicate an unsatisfactory customer

experience (Eilbacher Col. 11 lines 25-61).

Therefore, it would have been obvious to one of ordinary skill in the art at the

time of the invention to modify the system of Tsuchikawa in view of Soundararajan to

incorporate verifying that an agent requested a customer's permission to put the

customer on hold, wherein the pivot spot is the time the agent put the customer on hold,

the initial region of interest is the whole interaction, and wherein the region of interest is

defined by a first predetermined number of seconds prior to the pivot spot and a second

predetermined number of seconds following the hold as taught by Eilbacher to allow for

the monitoring of a customer and agent interaction, wherein various retrieval methods

are implemented based on responses (Eilbacher Col. 8 lines 29-67) and key locations

of media selected based on the customer responses (i.e. images, keywords, etc.) to

create and ideal/optimal retrieval of information (Eilbacher Col. 11 lines 25-61).

6.   Claims 10, 14, 15, 17, 18, 26, 30, and 32 rejected under 35 U.S.C. 103(a) as

being unpatentable over Tsuchikawa et al. US 5748775 A (hereinafter Tsuchikawa)

in view of Soundararajan US 20030106072 A1 (hereinafter Soundararajan) and

Eilbacher et al. US 6724887 B1 (hereinafter Eilbacher) further in view of Kung et

al. US 6917610 B1 (hereinafter Kung).

        Re claim 10, Tsuchikawa in view of Soundararajan and Eilbacher fails to teach

the apparatus of claim 1 further comprises a computer telephony interface events

analyzer component to identify and capture at least one common telephony events

associated with the interaction data

        Kung teaches an activity log may indicate using easy to understand icons as to

whether the communication is a telephone calls (e.g., record 831), a multimedia video

and audio calls (e.g., records 832 and 841), a text email (e.g., record 842), and/or an

instant message email (e.g., record 840), etc. Further, the activity log GUI may be

include a feature button 802 with a pull down menu that allows the subscriber to select

between combined media record listing, or one or more of the particular media types

such as telephone calls, multimedia video and audio calls, text emails, instant message

email, etc., to be displayed on the GUI at the same time. In addition, the activity log

may include records, such as record 833, of incoming communications which have no

known DN or address associated with them, when the originating party uses, for

example, a feature such as caller ID blocking (Kung Col. 33 lines 1-25).

Therefore, it would have been obvious to one of ordinary skill in the art at the

time of the invention to modify the system of Tsuchikawa in view of Soundararajan and

Eilbacher to incorporate invention a computer telephony interface to identify and capture

common telephony events as taught by Kung to allow for a restricted list of subscribers

that only have access to phone information (i.e. Caller ID blocking) (Kung Col. 33 lines

1-25).

Re claim 14, Tsuchikawa in view of Soundararajan fails to teach the apparatus of

claim 1 wherein the interaction is one of the following: a telephone call, and e-mail

message, an audio recording, a video, multimedia data or an interaction media.

Kung teaches an activity log may indicate using easy to understand icons as to

whether the communication is a telephone calls (e.g., record 831), a multimedia video

and audio calls (e.g., records 832 and 841), a text email (e.g., record 842), and/or an

instant message email (e.g., record 840), etc. Further, the activity log GUI may be

include a feature button 802 with a pull down menu that allows the subscriber to select

between combined media record listing, or one or more of the particular media types

such as telephone calls, multimedia video and audio calls, text emails, instant message

email, etc., to be displayed on the GUI at the same time. In addition, the activity log

may include records, such as record 833, of incoming communications which have no

known DN or address associated with them, when the originating party uses, for

example, a feature such as caller ID blocking (Kung Col. 33 lines 1-25).

Therefore, it would have been obvious to one of ordinary skill in the art at the

time of the invention to modify the system of Tsuchikawa in view of Soundararajan and

Eilbacher to incorporate interaction is one of the following: a telephone call, and e-mail

message, an audio recording, a video, multimedia data or an interaction media as

taught by Kung for the purposes of a universal control system fro various multimedia

equipment/data, wherein all multimedia can interface through a single distributed

storage media (Kung Col. 33 lines 1-25).

Re claim 15, Tsuchikawa in view of Soundararajan fails to teach the apparatus of

claim 14 wherein the interaction media is at least one data packet carrying voice or

other media over internet protocol.

Kung teaches an IP central station 200 may be configured to provide connectivity

for the broadband residential gateway 300 to the Internet 180 (e.g., World Wide Web

(www)), as well as connectivity to other external networks such as public switched

telephone network 160 and signaling system 7 (SS7) 170 for end-to-end voice,

multimedia, and data applications, for example voice over IP telephony. IP packets

traveling through the IP network provide for priority so that, for example, voice packets

are given priority over data packets to maintain certain VoIP telephony QoS

requirements and a leased line concept for packet traffic which may have an even

higher priority. However, the system is sufficiently flexible so that the priority can be

dynamically altered according to customer preferences, variable billing rates, traffic

patterns, and/or congestion (Kung Col. 7 lines 19-33).

      Therefore, it would have been obvious to one of ordinary skill in the art at the

time of the invention to modify the system of Tsuchikawa in view of Soundararajan and

Eilbacher to incorporate data packets carrying voice over IP as taught by Kung to allow

for the maintenance of telephony operations to assign priority for transmission data,

wherein various device can be used communicate simultaneously (i.e. phone, PC, etc.)

(Kung Col. 7 lines 19-33).

      Re claim 17, Tsuchikawa in view of Soundararajan fails to teach the apparatus of

claim 1 wherein the interaction meta-data (Kung Col. 33 lines 26-39) is an at least one

computer telephony integrated or CRM event.

      Kung teaches an activity log GUI may have a default set of categories which will

be displayed to the subscriber, e.g., which determines the type of information such as

the DN, a system address, an email address 808, a "contacted" party's name 809, a

company name 810, a client billing number 811, as well as billing information such as

the date 812, time 813, length of the previous communication (duration 815) and any

associated charges (cost 815) for the previous communication. Further, the GUI may

include a Category button 804 which enables the user to alter the information displayed

on the GUI and/or retained in the activity log. Thus, for example the user may alter the

activity log to include such as information as a contacted party's street address or include alternative DN's or system/email address (Kung Col. 33 lines 1-25).

Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to modify the system of Tsuchikawa in view of Soundararajan and Eilbacher to incorporate metadata as taught by Kung to allow for telephony or audio communication, wherein information about a conversation or video can be retained to allow for indexing of recognizable information such as a pattern or sequence of repetitive recorded characteristics (Kung Col. 33 lines 26-39).

Re claims 18 and 26, Tsuchikawa in view of Soundararajan fails to teach the apparatus of claim 1 wherein the interaction meta-data is associated with the at least one screen event.

Kung teaches an activity log GUI may have a default set of categories which will be displayed to the subscriber, e.g., which determines the type of information such as the DN, a system address, an email address 808, a "contacted" party's name 809, a company name 810, a client billing number 811, as well as billing information such as the date 812, time 813, length of the previous communication (duration 815) and any associated charges (cost 815) for the previous communication. Further, the GUI may include a Category button 804 which enables the user to alter the information displayed on the GUI and/or retained in the activity log. Thus, for example the user may alter the activity log to include such as information as a contacted party's street address or include alternative DN's or system/email address (Kung Col. 33 lines 26-39).

Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to modify the system of Tsuchikawa in view of Soundararajan and Eilbacher to incorporate interaction meta-data is associated with the at least one screen event as taught by Kung to allow for telephony or audio communication with the aid of visually seeing past data, wherein information about a conversation or video can be retained to allow for indexing of recognizable information such as a pattern or sequence of repetitive recorded characteristics (Kung Col. 33 lines 26-39).

Re claim 30, Tsuchikawa in view of Soundararajan fails to teach the method of claim 19 further comprises the steps of:

identifying an at least one pre-defined computer telephony integrated event in the interaction data (Kung Col. 33 lines 1-25);

identifying an at least one pre-defined screen event in the interaction data (Kung Col. 33 lines 26-39)

Kung teaches an activity log GUI may have a default set of categories which will be displayed to the subscriber, e.g., which determines the type of information such as the DN, a system address, an email address 808, a "contacted" party's name 809, a company name 810, a client billing number 811, as well as billing information such as the date 812, time 813, length of the previous communication (duration 815) and any associated charges (cost 815) for the previous communication. Further, the GUI may include a Category button 804 which enables the user to alter the information displayed on the GUI and/or retained in the activity log. Thus, for example the user may alter the

activity log to include such as information as a contacted party's street address or include alternative DN's or system/email address.

Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to modify the system of Tsuchikawa in view of Soundararajan and Eilbacher to incorporate identifying an at least one pre-defined computer telephony integrated event in the interaction data and identifying an at least one pre-defined screen event in the interaction data as taught by Kung to allow for telephony or audio communication with the aid of visually seeing past data, wherein information about a conversation or video can be retained to allow for indexing of recognizable information such as a pattern or sequence of repetitive recorded characteristics (Kung Col. 33 lines 1-25).

Re claim 32, Tsuchikawa in view of Soundararajan fails to teach the method of claim 19 further comprises performing an at least one content analysis step during the capturing of the interaction data and the interaction meta-data (Kung Col. 33 lines 26-39)

Kung teaches an activity log GUI may have a default set of categories which will be displayed to the subscriber, e.g., which determines the type of information such as the DN, a system address, an email address 808, a "contacted" party's name 809, a company name 810, a client billing number 811, as well as billing information such as the date 812, time 813, length of the previous communication (duration 815) and any associated charges (cost 815) for the previous communication. Further, the GUI may

include a Category button 804 which enables the user to alter the information displayed

on the GUI and/or retained in the activity log. Thus, for example the user may alter the

activity log to include such as information as a contacted party's street address or

include alternative DN's or system/email address.

Therefore, it would have been obvious to one of ordinary skill in the art at the

time of the invention to modify the system of Tsuchikawa in view of Soundararajan and

Eilbacher to incorporate performing an at least one content analysis step during the

capturing of the interaction data and the interaction meta-data as taught by Kung to

allow for telephony or audio communication with the aid of visually seeing past data,

wherein information about a conversation or video can be retained to allow for indexing

of recognizable information such as a pattern or sequence of repetitive recorded

characteristics (Kung Col. 33 lines 26-39).

7.   **Claims 12 and 27-29 rejected under 35 U.S.C. 103(a) as being unpatentable**

over Tsuchikawa et al. US 5748775 A (hereinafter Tsuchikawa) in view of

Soundararajan US 20030106072 A1 (hereinafter Soundararajan) and Eilbacher et

al. US 6724887 B1 (hereinafter Eilbacher) and further in view of Chase US 6332143

B1 (hereinafter Chase).

Re claims 12 and 27-29, Tsuchikawa in view of Soundararajan and Eilbacher

fails to teach the apparatus of claim 4, wherein the audio analyzer component further

comprises the elements of:

a word spotting component to locate and identify pre-defined terms or patterns in the speech elements of the interaction data (Chase Col. 17 lines 50-63);

an emotion analysis component to locate and identify positive or negative emotions in the interaction data (Chase Col. 11 lines 45-53);

a talk analyzer component to identify and locate specific pre-defined speech events in the speech elements of the information data (Chase Col. 17 lines 50-63 & Fig. 5 item 57)

Chase teaches an emotional descriptor that most closely matches the emotional connotation that the connotative judge associates with the word or phrase, considering the denotative context and part of speech, wherein a connotative judge understands the word or phrase and its denotative context, but does not associate any of the emotional descriptors from the supplied list of emotional descriptors with the word or phrase and its denotative context. Further, Chase teaches high level information of FIG. 5 includes a rating of the passage for emotional content in terms of positive emotion, negative emotion and global emotion (i.e., positive not distinct from negative emotion). The high level information also includes a rating of the passage for human interest by words, sentences and global content. a rating of the passage for power, a rating of the passage for activity and a rating of the passage along a scale of abstractness versus concreteness (Chase Col. 17 lines 50-63 & Fig. 5 item 57).

Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to modify the system of Tsuchikawa in view of Soundararajan and Eilbacher to incorporate a word spotting component to locate and identify pre-defined

terms or patterns in the speech elements of the interaction data, an emotion analysis

component to locate and identify positive or negative emotions in the interaction data,

and a talk analyzer component to identify and locate specific pre-defined speech events

in the speech elements of the information data as taught by Chase for the purposes of

understanding the context of a situation if there is no video available (Chase Col. 17

lines 50-63 & Fig. 5 item 57).

8.   **Claim 40 is rejected under 35 U.S.C. 103(a) as being unpatentable over**
Tsuchikawa et al. US 5748775 A (hereinafter Tsuchikawa) in view of
Soundararajan US 20030106072 A1 (hereinafter Soundararajan) and Eilbacher et
al. US 6724887 B1 (hereinafter Eilbacher) and further in view of Ronca US 6745221
B1 (hereinafter Ronca).

        Re claim 40, Tsuchikawa in view of Soundararajan and Eilbacher fails to teach

the method of claim 19 wherein optimizing the initial region of interest is performed by

choosing less resource extensive analysis to be performed prior to more resource

extensive analysis.

        Ronca teaches that a CPU trigger event agent 18 generates CPU trigger events

when CPU utilization is not available or not at an optimal rate. The resource usage

trigger event agent 20 generates resource usage trigger events when resources are not

available to handle applications and it is necessary to re-assign ports to handle the

applications. The call traffic trigger event agent 22 generates call traffic events when

the amount of incoming or outgoing traffic is higher or lower than a predetermined

threshold level. In the case of incoming or outgoing traffic above the threshold level, the call traffic trigger events signify a need for additional port allocation to handle the traffic. In the case of incoming or outgoing traffic below the threshold level, the call traffic trigger events signify additional port availability. The system clock trigger event agent 24 generates system clock trigger events at specific times of the day to signal peak and non-peak hours as well as business and non-business hours (Ronca Col. 5 lines 43-60).

Further, Ronca teaches the reassignment of resource allocation by the resource allocation manager 10 in response to a call traffic trigger event generated during peak hours is illustrated as a representative use case. In this case, high traffic above the threshold level is detected by the call traffic trigger event agent 22. The call traffic trigger event agent 22 in turn generates a call traffic trigger event 30 and conveys the call traffic event to the resource allocation engine 12. When the resource allocation engine 12 receives the call traffic trigger event, the resource allocation engine 12 accesses the resource allocation rules database 16 and checks 32 the resource allocation rules therein. Using the rules in Table 1, the resource allocation engine 12 generates a resource allocation directive 34 for the allocation agents 26 handling the ports of group 3. When the resource allocation agents 26 receive the resource allocation directive 34, they condition 36 their ports so that they become allocated to handle incoming applications (Ronca Col. 6 lines 8-28).

Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to modify the system of Tsuchikawa in view of Soundararajan and Eilbacher to incorporate optimizing the initial region of interest is performed by choosing

less resource extensive analysis to be performed prior to more resource extensive

analysis as taught by Ronca to allow for an optimal rate of event handling, wherein

threshold levels are implemented to handle call traffic in a voice response system to

allocate an optimal number of agents is available (Ronca Col. 5 lines 43-60).

9.   Claim 43 is rejected under 35 U.S.C. 103(a) as being unpatentable over

Tsuchikawa et al. US 5748775 A (hereinafter Tsuchikawa) in view of

Soundararajan US 20030106072 A1 (hereinafter Soundararajan) and Eilbacher et

al. US 6724887 B1 (hereinafter Eilbacher) and further in view of Bernard et al. US

5918213 A (hereinafter Bernard).

        Re claim 43, Tsuchikawa in view of Soundararajan and Eilbacher fails to teach

the method of claim 19 wherein the method is used for measuring the effectiveness of a

promotion offer to a customer requesting the termination of the service, wherein the

pivot spot is the time of a screen event related to offering a promotion or to an account

being saved or lost, and wherein the region of interest is defined by a first

predetermined number of seconds prior to the pivot spot.

        Bernard teaches that promotional items are offered to a customer 182 based on

his or her calling and purchasing history. For example, in one embodiment, the

automated product purchasing system review calling and purchasing statistics

maintained for a shopper 182. Statistics can be maintained by VRU 104, interactive

transaction database 112, or even by reporting database 438. If these statistics indicate

that the shopper is a particularly good customer of the automated product purchasing

system, interface unit 104 may offer a promotional or special item to that shopper 182.

For example, where shopper 182 is a frequent purchaser, interface unit 104 may inform

him or her that upon the next purchase, he or she will receive a bonus CD (Bernard Col.

51 lines 29-41).

Further, Bernard teaches a caller 182 decides to delete all of the items in his or

her virtual shopping cart, as indicated by input step 3724, VRU 104 simply deletes these

items from the order. This deletion step is illustrated by a step 3728. In one

embodiment this is accomplished by deleting all the order information from the previous

call and beginning anew with fresh order information for the present call. In an

alternative embodiment, the deletion is accomplished by simply removing the items'

catalog ID numbers 1008 from the order information in interactive transaction database

112. A confirmation script can be played by VRU 104 announcing that the order has

been canceled. As with the other options, at this time the caller is returned to the

shopping mode where he or she can sample additional selections or terminate the

phone call. Although not illustrated, in one embodiment, caller 182 is given the option of

hearing a listing of the items in his or her virtual shopping cart before deciding whether

to keep or cancel the order entirely. Finally, caller 182 may decide to individually review

the items in the virtual shopping cart and determine whether each individual item is to

be kept. If this is the case, caller 182 elects to review the items on hold as illustrated by

input step 3732. In response, in a step 3736, VRU 104 reviews the order with caller

182. In one embodiment, this is accomplished by a process similar to that illustrated in

FIG. 36 where each item is reviewed one at a time, and caller 182 selects whether to

accept or delete each item. Once the review order process is complete, caller 182 is forwarded to the shopping mode where he or she can sample additional selections, immediately purchase the selections remaining in his or her virtual shopping cart, or terminate the call (Bernard Col. 50 lines 1-32).

Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to modify the system of Tsuchikawa in view of Soundararajan and Eilbacher to incorporate measuring the effectiveness of a promotion offer to a customer requesting the termination of the service, wherein the pivot spot is the time of a screen event related to offering a promotion or to an account being saved or lost, and wherein the region of interest is defined by a first predetermined number of seconds prior to the pivot spot as taught by Bernard to allow for the automated and statistical determination of whether a promotional/coupon should be applied to a caller based on the callers history (Bernard Col. 51 lines 29-41), wherein an order can be cancelled based on a caller history (Bernard Col. 50 lines 1-32).

Conclusion

10.   The prior art made of record and not relied upon is considered pertinent to applicant's disclosure. US 6798786 B1, US 4351007 A, US 20040001437 A1.

11.   Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP

§ 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37

CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE

MONTHS from the mailing date of this action. In the event a first reply is filed within

TWO MONTHS of the mailing date of this final action and the advisory action is not

mailed until after the end of the THREE-MONTH shortened statutory period, then the

shortened statutory period will expire on the date the advisory action is mailed, and any

extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of

the advisory action. In no event, however, will the statutory period for reply expire later

than SIX MONTHS from the date of this final action.

Any inquiry concerning this communication or earlier communications from the

examiner should be directed to Michael C. Colucci whose telephone number is (571)-

270-1847. The examiner can normally be reached on 9:30 am - 6:00 pm, Monday-

Friday.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Richemond Dorvil can be reached on (571)-272-7602. The fax phone

number for the organization where this application or proceeding is assigned is 571-

273-8300.

Information regarding the status of an application may be obtained from the

Patent Application Information Retrieval (PAIR) system. Status information for

published applications may be obtained from either Private PAIR or Public PAIR.

Status information for unpublished applications is available through Private PAIR only.

For more information about the PAIR system, see http://pair-direct.uspto.gov. Should

you have questions on access to the Private PAIR system, contact the Electronic

Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a

USPTO Customer Service Representative or access to the automated information

system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/Michael C Colucci/
Examiner, Art Unit 2626
Patent Examiner
AU 2626
(571)-270-1847
Michael.Colucci@uspto.gov
/Richemond Dorvil/
Supervisory Patent Examiner, Art Unit 2626